

# DRIVE REVENUE WITH SUPERIOR TECHNOLOGY.

The Refresher Oasis was built for long days and busy events with its industry-leading can capacity and enough merchandising space for all your most popular items. With an ELiTE® lithium drivetrain powered by Samsung SDI battery technology or a fuel-efficient 13.5 hp EFI gas engine, the Refresher Oasis pushes unparalleled customer service.

**500 CAN** 

CAPACITY

12.1 SQ FT

COUNTER SPACE

6.7 CU FT

MERCHANDISE CABINET









### **ELITE LITHIUM POWERTRAIN**

- Zero Maintenance Battery
- 5-Year Battery Warranty
- Lightweight Footprint
- Increased Efficiency
- Upgrade to 6.2 Triple Pack for Extended Range
- Automatic Park Brake
- Multifunction SOC/ Speedometer Gauge
- Limited Slip Differential

#### **OPTIONS & ACCESSORIES**

- Trash/Recycle Bins
- Aluminum Canopy Frame
- Color Options Available for Canopy, Unit & Vehicle
- 3.0 Liter Airpots (2)
- Reversible Airpot Holder
- Humidor
- Consumable Ice Bin
- NSF Rated Ice Sink
- Unique Drainage
- Wheel Covers
- Turf Tires
- USB Outlet
- Glove Box Door and Shelf
- LED Headlights
- LED Taillights/Brake Lights
- Rapid On-Board Charger)
- Additional Body Colors
- Limited Slip Differential

CUSHMAN.COM

## REFRESHER OASIS

**ELITE LITHIUM** 

Welded Steel with E-Coat & DuraShield™ Powder Coat

**EFI GAS** 

### **BODY & CHASSIS**

FRAME

BODY & FINISH	Injection Molded TPO, Painted (Front)	
STANDARD COLOR	Forest Green	
DIMENSIONS		
DIMENSIONS		
OVERALL LENGTH	117.0 in (297.18 cm)	
OVERALL WIDTH	50.8 in (129.032 cm)	
OVERALL HEIGHT (NO CANOPY)	47.4 in (120.40 cm)	
OVERALL HEIGHT (WITH CANOPY)	73.3 in (186.18 cm)	
WHEEL BASE	76 in (193.04 cm)	
FRONT WHEEL TRACK	35 in (88.90 cm)	
REAR WHEEL TRACK	38.5 in (97.79 cm)	
GROUND CLEARANCE	4.5 in (11.43 cm)	
REFRESHER UNIT MATERIAL AND FINISH	5000 Series Aluminum - Super Durable TGIC Polyester Powder Coating	

D	n	W	V	E	E
	u	v	v	6	г

POWER SOURCE	56.7 V Li-Ion Battery	4 Cycle 24.5 cu in (401 cc)	
MOTOR TYPE	AC Induction	N/A	
VALVE TRAIN	N/A	Single Cylinder OHV	
HORSEPOWER (KW)	14.9 hp (11.1 kW)	13.5 hp (10.1 kW)	
ELECTRICAL SYSTEM	48V Primary, 12V Auxiliary	Starter/Generator, Solid-State Regulator	
BATTERY (QTY/TYPE)	4.2 ELiTE - Twin Pack	One 12 Volt Maintenance Free	
BATTERY CHARGER	811 Watt World Charger	N/A	
KEY OR PEDAL START	Pedal		
AIR CLEANER	N/A	Industrial Rated Dry Filter	
LUBRICATION	N/A	Pressurized Oil System	
OIL FILTER	N/A	Spin-On	
COOLING SYSTEM	N/A	Air Cooled	
FUEL CAPACITY	N/A	6.65 Gallon (25 L) tank	
DRIVE TRAIN	Motor Shaft Direct Drive	Continuously Variable Transmission (CVT)	
TRANSAXLE	Limited-Slip Differential with Helical Gears	Differential with Helical Gears	
GEAR SELECTION	Forward-Neutral-Reverse	Forward-Reverse	
REAR AXLE RATIO	16.99:1	16.53:1 (Forward) 16.81:1 (Reverse)	

### PERFORMANCE

2-Person		
21.5 ft (6.5 m)		
11 mph ± 0.5 mph (17.7 kph ± 0.8 kph)		

### STEERING & SUSPENSION

STEERING	Self-Compensating Rack and Pinion		
FRONT/REAR SUSPENSION	Leaf Springs with Hydraulic Shock Absorbers		
SERVICE BRAKE	Rear Wheel Mechanical Self-Adjusting Drum		
PARKING BRAKE	Automatic Electro-Magnetic	Self-Compensating, Single Point Engagement	
TIRES	18 x 8.5-8		

