

# GP400 DIESEL

## VERSATILE RIDE-ON REEL MOWER



- **TIGHT FREQUENCY OF CLIP USING JAKE'S 15 BLADE REEL**
- **TRUSTWORTHY KUBOTA ENGINE**
- **REELS CONFIGURED FOR FINE SPORTS TURF**
- **UNIQUE SWING OUT CENTER CUTTING UNIT FOR EASE OF SERVICE**

CUT WIDTH  
**62"**  
(1.6M)

CUT HEIGHT  
**0.062" - 0.438"**  
(1.6MM - 11.1MM)

CUTTING CAPACITY  
**2.37<sup>AC</sup>**  
(0.96HA) / HR  
(1.6M X 6KM / HR)

FUEL CAPACITY  
**15<sup>GAL</sup>**  
(58.6L)

MOWER ENGINE  
**KUBOTA<sup>®</sup>**  
**17.7HP**  
(13.2KW) DIESEL

BLADES PER REEL  
**7, 9, 11**  
**OR 15**

The GP400 Diesel is a versatile ride-on reel mower. With the tightest frequency of clip, using Jake's 15 blade reel, along with a trustworthy Kubota® engine, everything has been designed to assist you. The GP400 offers our greatest reel section, configured for fine sports turf. A swing-out center unit and easy maintenance get the mower on the golf course quickly.

Adjustable Reel Drop and Adjustable Reel Sequence along with simple operation and ergonomically designed controls keep you there until the work is done.



SINCERELY

Jake

For information and support:  
[www.jacobsen.com](http://www.jacobsen.com) / +44 (0) 1473 270 000 / +1-888-438-3946



Actual operating power output may vary due to conditions of specific use. Run time will vary based on conditions of specific use, accessories, and terrain. NOTE: Specifications, while correct at time of printing, may change without notice.

© 2021 Textron Specialized Vehicles Inc.

# GP400 DIESEL

## VERSATILE RIDE-ON REEL MOWER



Ergonomically designed dash panel incorporating joystick controls

Headlights

Front reel soft-drop

ROPS as standard

Rear cutting unit sequencing

Easy access grill

Automotive handbrake

On-board backlapping



Reels configured for fine sports turf



Unique swing out center cutting unit for ease of service



Trustworthy Kubota® engine

### REELS & BLADES

NUMBER AND SIZE	3 x 22" (55.88cm) reels; 5" (12.7cm) diameter
BLADE MATERIAL	Hardened high carbon steel
CUTTING UNIT LIFT	Hydraulic double action cylinders; parallel link head leveling system
CUTTING FREQUENCY	7 Blade: 0.079"/mph (1.24mm/km/h), 15 Blade: 0.037"/mph (0.58mm/km/h)

### TRACTION, BRAKES & SPEED

TRACTION DRIVE	Hydraulic motor on each drive wheel, optional 3WD
REEL DRIVE	Gear-type hydraulic motor; backlap control valve standard
HYDRAULIC SYSTEM	6.8gal. (25.7 L) capacity; 10 micron, full-Flow Filtration; biodegradable hydraulic fluid; oil cooler standard
SERVICE BRAKES	Hydrostatic braking
PARKING BRAKES	6" (152mm) caliper disc, hand operated
STEERING	Power Steering
MOWING SPEED	3.7mph (6km/h)
TRANSPORT SPEED	0 - 7.5mph (0 - 12km/h)

### WEIGHTS & DIMENSIONS

WEIGHT (excluding fuel)	1388 - 1746lb (630 - 792kg)
LENGTH	83" (2.12m)
OVERALL HEIGHT (including ROPS)	67.7" (1.72m)
WHEELBASE	51.2" (1.30m)
TRANSPORT WIDTH	74.5" (1.89m)
WORKING WIDTH	74.5" (1.89m)

### WARRANTY

MOWER WARRANTY	2 Years
----------------	---------

### ACCESSORIES

- 55.9cm (22") Front rollers ranging from 5.1cm (2") to 5.7cm (2½") – solid tube steel, grooved assembled or machined aluminum or steel
- Grass catcher kit (new Eclipse style)
- Turf Groomer®
- Quick roll greens roller (set of 3)
- Spiker attachment w/ frame assembly
- 22" (55.9cm) front roller fine bristle brush
- Powered rear roller brush for 12.7 x 55.9cm (5" x 22") cutting unit
- High cut kit – 2.4cm (¾") when used with .5cm (2¾") roller
- GP400 3WD kit
- Automatic mow speed selection kit